



Beam scale

Type : KPZ 1B

For continuous operation


Maintenance free

Long service life

Robust

Inexpensive

Mobile



Dimension in mm

solid plug connection

German quality construction

(pharmaceutical version on request)

Weighing range from 0 up to 6000 kg

Beam scale type: KPZ 1B for use with or without EU approval.

High quality steel construction, black powder painted, made of rectangular pipe 120 x 60 x 4 mm with transport rollers and handle for comfortable transport.

Load cells: High quality load cells DMS type KPZ 502E-2, IP 67, OIML C3. **Indicator:** 51E-8, with two 5 meter cable, sheltered at way out of scale in case of mechanical damage.

Certification: EC approval possibility class III, Declaration of Conformity.

Type	Capacity	Division	Dim. mm	Approval	Art-Nr.
KPZ 1BM	1500/3000 kg	500/1000 g	85 x 1000	No	1BM000103000
KPZ 1BE	1500 kg	500 g	85 x 1000	Yes	1B000010150E
KPZ 1BE	3000 kg	1000 g	85 x 1000	Yes	1B000010300E
KPZ 1BM	1500/3000 kg	500/1000 g	85 x 1260	No	1BM000123000
KPZ 1BE	1500 kg	500 g	85 x 1260	Yes	1B000012150E
KPZ 1BE	3000 kg	1000 g	85 x 1260	Yes	1B000012300E
KPZ 1BM	1500/3000 kg	500/1000 g	85 x 1500	No	1BM000153000
KPZ 1BE	1500 kg	500 g	85 x 1500	Yes	1B000015150E
KPZ 1BE	3000 kg	1000 g	85 x 1500	Yes	1B000015300E

In above mentioned products KPZ applies only EU approved components 

Other dimensions, capacities, options and divisions on request.

Calibration protocol as option. Price on request.

Option: Cash register system connection!

2 Range
division

Construction : rectangular pipe 120 x 60mm, black powder painted (option: galvanized or stainless construction). Dimension: 1000x120x85 , 1250x120x85 1500x120x85mm. With transport rollers and handle for easy transport. Indicator connection cable: length 5 m. Special flat construction is suitable for ground placing. With regard to solid DMS load cells there are no wearing out parts. Possibility to deliver other dimensions.

Weighing system: 4 high quality DMS load cells KPZ 502E-2, IP67, EC approval possibility class III.



Standard Indicator

Built in a stable, robust steel housing, easy to operate keyboard, covered with a dust- and waterproof foil, large function keys, 6 digit LCD-Display with backlight function, easy readable 30mm high digits.

Function: Zero setting, 100% Tare (Multiple tare possible), minus indication, reference piece counting and summing the weights.

Menu settings: Weight set-point control, LOW battery , automatic shut-off, peak measured value or weight hold function. Self-test function.



M

Standard indicator KPZ 51E-8: easy and comfortable maintenance, solid, robust ABS housing, keyboard covered with a dust- and water-proof foil, with large function keys. Large LCD-Display with backlight allows proper weighing result read-out, to use with almost every industrial conditions.

Functions : Zero, 100% tare (also multiple tare), minus indication, switch Net and Gross weight. Options to set via menu: target weight check tolerance, limit value control (limit= range of Low/Ok/High), automatic self test.

Indication : weight, zero setting, tare, stability, charging status, LOW-Bat indication, limit value control.

Power supply: 230 V, battery version (option).

KNORRING OY AB

Karvaamokuja 6, PL20

00380 HELSINKI

puh. 09-56041, fax 09-5652463

e-mail: knorring@knorring.fi

web: www.knorring.fi

Jyväskylä: puh. 014-614100

Turku: puh. 02-4355158

