




Pallet Scale

Type : KPZ 1 N

For continuous operation
Stainless steel - Material 1.4301

Robust
Inexpensive
Mobile
Maintenance free



Dimension in mm

German quality construction
(pharmaceutical version on request)
Weighing range from 0 up to 6.000 kg

Pallet scale type: KPZ 1 N for use with or without EU approval.

Very robust and stable **stainless steel construction (material DIN 1.4301)** made of rectangular pipe 120 x 60 x 4 mm with transport rollers and handle for comfortable transport. **Load cells:** high quality **DMS load cells stainless steel** type 502E-2, IP 68 (standard), OIML C3. Movable feet with adjustable height made of stainless steel. **Indicator:** KPZ 51E-9-1 (possibility to deliver without indicator), with 5 m cable, sheltered at way out of scale in case of mechanical damage. **Certification:** EC approval possibility class III, Declaration of Conformity.

| Type | Capacity | Division | Dim. mm | Approval possible | Article-No. |
|----------------|---------------------|------------------|-------------------|-------------------|---------------------|
| KPZ 1EN | 600 kg | 200 g | 840 x 1260 | Yes (III) | 1N00000060E |
| KPZ 1EN | 1500 kg | 500 g | 840 x 1260 | Yes (III) | 1N000000150E |
| KPZ 1EN | 2.000 kg | 1000 g | 840 x 1260 | Yes (III) | 1N000000200E |
| KPZ 1NM | 1500/2000 kg | 500/1000g | 840 x 1260 | No | 1NM000002000 |
| KPZ 1EN | 3000 kg | 1000 g | 840 x 1260 | Yes (III) | 1N000000300E |
| KPZ 1NM | 1500/3000 kg | 500/1000g | 840 x 1260 | No | 1NM000003000 |

Attention! Price does NOT include certification. Price: Ex works KPZ Poland

KPZ 1 N price includes indicator KPZ 51E-9-1

In above mentioned products KPZ applies only EU approved components

Other dimensions, capacities, options and divisions on request.

Calibration protocol as option. Price on request.

Option: Cash register system connection!



2 Range
division

Construction : stainless steel, rectangular profile 120 x 60mm, material 1.4301. Dimension: (outside) 840 x 1260mm with handle 1340mm (inside) 600 x 1140mm. With transport rollers and handle for easy transport.

Weighing system: 4 precision DMS load cells, stainless steel, indicator connection cable, length: 5m. With regard to solid DMS load cells there are no wearing out parts.



M

Indicator KPZ 51E-9-1

Stainless steel housing IP 67,

6 digit 25 mm high LCD-Display,

with backlight function, large function keys

Pre-set / limit value control

Simple piece counting

EC approved class (III) **up to 10.000 e**

Description: solid stainless steel housing **IP 67**, user-friendly, large function keys. LCD display: 6 digit, various symbols, backlight. Operating temperature from -10°C up to +40°C.

Power supply: 230 V, battery version (option).

Functions: automatic and manual zero setting, switch Net/Gross weight, 100% tare, multiple tare, unit switching, simple piece counting by reference no. 10, 20, 50, 100 i 200. Minus indication, LCD backlight, automatic shutoff after 0-9 minutes, pre-set value control or limit value control LOW – OK - HIGH (any two Weight values to choose, tone or light signal), electronic stabilization filter, automatic self test, error messages.

Indication: zero setting, gross, net, stability, LOW-Bat indication, pre-set/limit value, too small piece quantity or too small weight.

LED: charging status.

Weighing system: 4 precision DMS load cells, stainless steel, IP 68, EC approved class III.

Options

KPZ 1N pallet scale stainless steel (material DIN 1.4301)

| Options / accessories / extra charge | | Article-No. |
|--|-------------------------|--------------------|
| Indicators: Options (extra cost) | | |
| Delivery without Indicator KPZ 51E-9-1 | REDUCED PRICE | 12N51E91OHNE |
| Indicator KPZ 51E-9-2, Stainless steel housing (IP 67), High/OK/LOW, 10 Memory | | 12N51E920000 |
| Printers: Options (extra cost) + costs for output RS 232 | | |
| Roller printer FAVORIT Plus, for KPZ 51E-*, Thermoprinting | | 120024000000 |
| Rollerprinter DR 3-1 for KPZ 51E-*, 56E-1, with addition | | 120035100000 |
| Label printer and code printer type DR 2 for KPZ 56E-1, KPZ 51E-9-2 | | 120034000000 |
| Print design for DR 2 on request | | 204333100000 |
| serial interface / Setpoints: Options / extra costs | | |
| Serial interface RS232 C for KPZ 51E-9-1 | | 123071000000 |
| Serial interface RS232 C for KPZ 51E-9-2 | | 123072000000 |
| Setpoints, 3 pcs for KPZ 51E-9-2 (more – OK – less) | | 120029002000 |
| Standard-Programm – Software in connection with RS232 | | 51E003340000 |
| Wi-Fi Datatransfer | | 120005000000 |
| Rechargeable battery version KPZ 51E-9-1, 51E-9-2 | | 120040000000 |
| weights & measures certification (extra charge) | | |
| KPZ Factory first certification from 550 kg up to 3.000 kg | | 300116000000 |
| For Printer | | 300118000000 |
| construction accessories (extra charge) | | |
| Indicator stand for KPZ 51E-9-1, 51E-9-2 Stainless Steel | | 1N0200000000 |
| Packing dimension | | |
| Model | Dimension | |
| KPZ 1 | 130 x 84 x 50 cm, 80 kg | |
| <i>We reserve the right to make changes without prior notification</i> | | |

KNORRING OY AB

Karvaamokuja 6, PL20

00380 HELSINKI

puh. 09-56041, fax 09-5652463

e-mail: knorring@knorring.fi

web: www.knorring.fi

Jyväskylä: puh. 014-614100

Turku: puh. 02-4355158

