



Ergonomic design and external sensor for highest ease of use

Features

- **External sensor** for difficult-to-access measurements
- **Data interface RS-232**, included
- **Base plate and calibration foils** included
- **1 Delivered in a robust carrying case**
- **Offset-Accur:** This function allows you to adjust the instrument precisely on the locally measured range by a two-point calibration. This results in a superior accuracy of approx. 1 % of the measured value
- **Selectable measuring units:** µm, mil
- **Auto-Power-Off**

Technical data

- Precision:
  - Standard: 3 % of measured value or ± 2,5 µm
  - Offset-Accur: 1 % of measured value or ± 1 µm
- Smallest sample surface (radius)
  - Type F:
    - Convex: 1,5 mm
    - Concave: 25 mm
  - Type N:
    - Convex: 3 mm
    - Concave: 50 mm
- Minimal base thickness: 0,3 mm
- Dimensions W×D×H 65×28×131 mm
- Battery operation, batteries standard 4× 1.5V AAA
- Net weight approx. 81 g

Accessories


- **Data transfer software**, interface cable included, SAUTER ATC-01
- **Calibration foils** for increased measuring accuracy (covers the range from 20 up to 2000 µm, with < 3 % tolerance), SAUTER ATB-US07
- **2 External sensor**, TypeF, SAUTER ATE 01
- **3 External sensor**, TypeN, SAUTER ATE 02


STANDARD


 CAL BLOCK

 FOCUS


 RS 232

 ZERO

 BATT


























 1 DAY

OPTION

 SOFTWARE

 ISO +4 DAYS

Model	Measuring range [Max] µm	Readout [d] µm	Test object	Option Factory calibration certificates	
				KERN	
SAUTER					
TE 1250-0.1F.	100   1250	0,1   1	Non-magnetic coatings on iron, steel (F)	961-110	
TE 1250-0.1N.	100   1250	0,1   1	Insulating coatings on non-magnetic metals (N)	961-110	
TE 1250-0.1FN.	100   1250	0,1   1	Combination instrument: F/N	961-112	

 <b>Adjusting program (CAL):</b> For quick setting of the balance's accuracy. External adjusting weight required.	 <b>Control outputs (optocoupler, digital I/O):</b> to connect relays, signal lamps, valves, etc.	 <b>Rechargeable battery pack:</b> rechargeable set.
 <b>Calibration block:</b> standard for adjusting or correcting the measuring device.	 <b>Analogue interface:</b> to connect a suitable peripheral device for analogue processing of the measurements.	 <b>Mains adapter:</b> 230V/50Hz in standard version for EU. On request GB, AUS or USA version available.
 <b>Peak hold function:</b> capturing a peak value within a measuring process.	 <b>Statistics:</b> using the saved values, the device calculates statistical data, such as average value, standard deviation etc.	 <b>Power supply:</b> Integrated, 230V/50Hz in EU. More standards e.g. GB, AUS or USA on request.
 <b>Scan mode:</b> continuous capture and display of measurements.	 <b>PC Software:</b> to transfer the measurements from the device to a PC.	 <b>Motorised drive:</b> The mechanical movement is carried out by a electric motor.
 <b>Push and Pull:</b> the measuring device can capture tension and compression forces.	 <b>Printer:</b> a printer can be connected to the device to print out the measurements.	 <b>Motorised drive:</b> The mechanical movement is carried out by a synchronous motor (stepper).
 <b>Length measurement:</b> captures the geometric dimensions of a test object or the movement during a test process.	 <b>GLP/ISO record keeping:</b> of measurements with date, time and serial number. Only with SAUTER printers.	 <b>Fast-Move:</b> the total length of travel can be covered by a single lever movement.
 <b>Focus function:</b> increases the measuring accuracy of a device within a defined measuring range.	 <b>Measuring units:</b> Weighing units can be switched to e.g. non-metric at the touch of a key. Please refer to website for more details.	 <b>DAkkS calibration possible:</b> The time required for DAkkS calibration is shown in days in the pictogram.
 <b>Internal memory:</b> to save measurements in the device memory.	 <b>Measuring with tolerance range (limit-setting function):</b> Upper and lower limiting can be programmed individually. The process is supported by an audible or visual signal, see the relevant model	 <b>Factory calibration:</b> The time required for factory calibration is specified in the pictogram.
 <b>Data interface RS-232:</b> bidirectional, for connection of printer and PC.	 <b>ZERO:</b> Resets the display to "0".	 <b>Package shipment:</b> The time required for internal shipping preparations is shown in days in the pictogram.
 <b>Data interface USB:</b> To connect the balance to a printer, PC or other peripheral devices.	 <b>Battery operation:</b> Ready for battery operation. The battery type is specified for each device.	 <b>Pallet shipment:</b> The time required for internal shipping preparations is shown in days in the pictogram.
 <b>Data interface Infrared:</b> To transfer data from the balance to a printer, PC or other peripheral devices.		

**Your SAUTER specialist dealer:**