



EcoMet™ 30

Grinder - Polisher

EcoMet™ 30

Grinder-Polisher Systems





EcoMet 30
Semi-Automatic
Single and Twin



EcoMet 30 Features

The EcoMet 30 family provides simple operation for routine grinding and polishing. The comfortable splash guard design allows for excellent control during manual grinding. The semi-automatic units are controlled with a touchscreen interface. All regularly used functions are accessed on the front screen with no complicated menus that can add time to the process. The EcoMet 30 saves time with advanced cleaning features. The all metal casting is durable and stable for use in busy lab environments.

Grinding & Polishing Made Simple



**EcoMet 30
Manual
Single and Twin**




Easy to Use

User Friendly TouchScreen

The EcoMet 30 Semi-Automatic provides simple operation for grinding and polishing with a user-friendly touchscreen interface. All regularly used functions are on the front screen without complicated menus.

Easy Specimen Loading

The EcoMet 30 Semi-Automatic system has a swing out head and easy load specimen holders to save time when accessing samples between preparation steps.



Durable

The EcoMet 30 was designed and extensively tested in continuous use laboratories. The robust cast aluminum platform used on both the Semi-Automatic and Manual models greatly enhances performance and durability.

Rinse & Spin Function

A rinse and spin function is included on the semi-automatic versions to prevent cross contamination between polishing steps. At the touch of a button the rinse and spin function will turn on the water, spin the platen at a user defined speed for a user defined time. The water is turned off during the last 10 seconds of the cycle to remove excess water in preparation for the next polishing step.




On the main screen, press and hold the "Rinse and Spin" button to begin the cycle.

Burst Dispensing

The EcoMet 30 Semi-Automatic units can be connected to the Burst Dispensing System for increased throughput in the lab. The Burst will automatically dispense during the cycle allowing a user to operate other machines during the polishing process.





Simple Cleaning

Easy to Remove Platen


Deep clean more frequently and prevent cross contamination with our easy to remove platen. Simply lift the platen to remove it from the machine without any tools to access the bowl for cleaning.




Quick Clean Bowl Liner

With the platen removed, simply rinse or replace the bowl liner and place back into the bowl. Insert the platen and begin polishing.





Ergonomic Design



Large flat work space and ergonomic bowl height provides better control and more comfort for manual polishing. The additional control improves sample quality and reduces grinding time.

Straight Drain System

Minimizes debris build up and saves cleaning time.



Low force switches and large touchscreen buttons provide an easy to reach and easy to see solution for all lab users.


Ordering Information

Get Started

Four models are available to meet lab needs. All models come with a Bowl Liner(s).


EcoMet 30 Manual (49-10070)

EcoMet 30 Manual Twin (49-10072)




EcoMet 30 Semi-Automatic (49-10075)

EcoMet 30 Semi-Automatic Twin (49-10076)



Add a Platen Kit

Platen kits include a platen, splash guard and cover. All EcoMet 30 models are capable of running 8in [203mm], 10in [254mm] or 12in [305mm] platens.



8in [203mm] Platen Kit
(49-1008)

10in [254mm] Platen Kit
(49-1010)

12in [305mm] Platen Kit
(49-1012)

Replacement Bowl Liners

Each EcoMet 30 ships with a Bowl Liner for each bowl. Order additional Bowl Liners to replace the original Bowl Liner.




Bowl Liner (Qty 5)
49-1005



Technical Specifications

| | EcoMet 30 Manual | EcoMet 30 Manual Twin | EcoMet 30 Semi Auto | EcoMet 30 Semi Auto Twin |
|------------------------------------|---|---|---|---|
| Machine Power | 100-240VAC, 50/60Hz, 1 phase | | | |
| Motor Power | 300W | 440W | | |
| Platen Diameter | 8in [203mm], 10in [254mm], 12in [305mm] | | | |
| Platen Wheel Speed | 50-500rpm stepless speed regulation | | 50-500rpm in 50rpm increments | |
| Wheel Direction | Counter-Clockwise | | Platen: Counter-Clockwise, Head: Clockwise/Counter-Clockwise | |
| Power Usage | 0.64kW, 5.6/2.78A @115/230VAC | 0.97kW, 8.5/4.1A @115/230VAC | 1kW, 8.8/4.3A @115/230VAC | |
| Control Panel | Membrane with switch switch | | Full color LCD Screen, 7in [75mm] diagonal | |
| Water Supply Pressure | 40-116 psi (2.7-8 bar) | | | |
| Water Supply Hose | 0.25in [6mm] OD tube | | | |
| Sound Rating | 65dB @ 500rpm | | 65dB @ 500rpm & 200rpm head | |
| Head Motor Power | 300W | | | |
| Weight | 102lbs [46kg] | 154lbs [70kg] | 165 lbs [75kg] | 231.5 lbs [105kg] |
| Dimensions (L x D x H) | 19.7in x 25.6in x 17.7in [500mm x 650mm x 450mm] | 37.4in x 26in x 17.7in [950mm x 660mm x 450mm] | 19.7in x 25.6in x 25.6in [500mm x 650mm x 650mm] | 37.4in x 26in x 25.6in [950mm x 660mm x 650mm] |
| Head Wheel Speed | 30-200rpm in 10rpm increments | | | |
| Central Specimen Force | 5-40lbs [25-200N] | | | |
| Single Specimen Force | 1-10lbs [5-40N] | | | |
| Central Force Specimen Capacity | 1in, 1.25in, 1.5in, 25mm, 30mm, 40mm | | | |
| Single Force Specimen Capacity | 1in, 1.25in, 1.5in, 25mm, 30mm, 40mm | | | |
| Air Supply Hose | 0.25in [6mm] OD tube | | | |
| Air Supply Pressure | ≥0.4Mpa [58 psi], [4 bar] | | | |
| Compliance | CE Directives | | | |



EcoMet 30 Accessories

Sample holders are designed to facilitate process automation and optimization. Many options for different sample sizes and shapes are available depending on the shapes, sizes, and capacities required.

Single Force Specimen Holders

○ Round/Barrel
□ Rectangle
 Slides
 Teardrop

For use with 60-9005 Drive Adapter

| Part Number | Style | Size | Capacity | Additional Accessories |
|-------------|-------|--------|----------|-----------------------------------|
| 60-10060 | ○ | 1in | 4 | 63-1022 Retaining Rings (Qty 6pk) |
| 60-10061 | ○ | 1.25in | 4 | 63-1023 Retaining Rings (Qty 6pk) |
| 60-10062 | ○ | 1.5in | 4 | 63-1024 Retaining Rings (Qty 3pk) |
| 60-10063 | ○ | 25mm | 4 | 63-1022 Retaining Rings (Qty 6pk) |
| 60-10064 | ○ | 30mm | 4 | 63-1023 Retaining Rings (Qty 6pk) |
| 60-10065 | ○ | 40mm | 4 | 63-1024 Retaining Rings (Qty 3pk) |





Central Force Specimen Holders

○ Round/Barrel
□ Rectangle
 Slides
 Teardrop




For use with 60-9000 Drive Adapters

Uses Loading Plates 60-2411 or 60-2413, 130mm diameter for 8", 10" or 12" platens

| Part Number | Style | Size | Capacity |
|-------------|---|--------------------------------|----------|
| 60-2482 | ○ | 1in | 6 |
| 60-2483 | ○ | 1.25in | 6 |
| 60-2484 | ○ | 1.25in | 3 |
| 60-2422 |  | 1.25in [32mm] | 6 |
| 60-2485 | ○ | 1.5in | 3 |
| 60-2486 | ○ | 30mm | 6 |
| 60-2487 | ○ | 40mm | 3 |
| 60-2409 | □ | 1 x 1.25in [25.4 x 31.75mm] | 4 |



Uses loading plates 60-2411 or 60-2412 157mm diameter for 10" or 12" platens

| | | | |
|---------|---|-----------|----|
| 60-8240 |  | 18 - 51mm | 5 |
| 60-8210 |  | 12 - 40mm | 6 |
| 60-8262 |  | 10 - 25mm | 12 |
| 60-8254 | □ | 55 x 30mm | 5 |
| 60-8255 | □ | 70 x 40mm | 3 |



Accessories for Specimen Holders

Loading Fixtures and Plates



Used for loading Central Force Specimen Holders to ensure planar samples.

| Part Number | Description |
|-------------|--|
| 60-2410 | Loading Fixture |
| 60-2411 | Loading Plate for 130mm and 157mm diameter |
| 60-2412 | Loading Plate for 157mm and 181mm diameter |
| 60-2413 | Loading Plate for 130mm and 181mm diameter |

Drive Adapters



Pairs specimen holders to the chuck of the automatic head

| Part Number | Description |
|-------------|---------------|
| 60-9000 | Central Force |
| 60-9005 | Single Force |

Independent Burst Dispensing System for EcoMet 30


The Burst Dispensing System is a flexible, easy to operate dispensing system for all diamond and final polishing suspensions. This product improves both productivity and consistency by dispensing suspensions at fixed intervals and configurable rates.




For Semi-Automatic units, utilize the connection cable to connect up to 3 Burst modules.

For Manual units, activate dispensing directly on the Burst module or use the Hand Switch.

| Part Number | Description |
|-------------|---|
| 40-10005 | Burst Module |
| 40-2823 | Hand Switch |
| 00-10100 | Stir Bar (optional) |
| 40-2704 | Connection Cable for semi-Automatic units |



Buehler Worldwide Locations



Lake Bluff, IL, US
Binghamton, NY, US
Norwood, MA, US
Coventry, UK
Dardilly, FR
Esslingen, DE
Hong Kong, CN
Shanghai, CN
Tokyo, JP



BUEHLER

Solutions for Materials Preparation, Testing and Analysis

BUEHLER

41 Waukegan Road, Lake Bluff, Illinois 60044

P: +1 847 295 6500 | 800 BUEHLER (800 283 4537)

W: www.buehler.com | **E:** info@buehler.com

North America-South America Offices

BUEHLER Worldwide Headquarters

P: +1 847 295 6500 | 800 BUEHLER (800 283 4537)

W: www.buehler.com | **E:** info@buehler.com

Europe Offices

BUEHLER Germany - Esslingen

ITW Test & Measurement GmbH

European Headquarters

P: +49 (0) 711 4904690-0

E: info.eu@buehler.com

BUEHLER France - Dardilly

P: +33 (0) 800 89 73 71

E: info.eu@buehler.com

BUEHLER United Kingdom - Coventry

P: +44 (0) 800 707 6273

E: info.eu@buehler.com

Asia-Pacific Offices

BUEHLER China - Shanghai

ITW Test & Measurement (Shanghai) Co., Ltd.

Asia Headquarters

P: +86 400 111 8683

E: info.cn@buehler.com

BUEHLER Japan

P: +81 03 5439 5077

E: info.japan@buehler.com

BUEHLER Asia-Pacific

P: +852 2307 0909

E: info.asia@buehler.com

Visit www.buehler.com for more information on a Buehler location near you.